



## DUO-SPOT MODULE

The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

**Categories:** [Refurbishment and Retrofit Fixtures](#)



The Duo-spot module is a rectangular panel equipped with two adjustable LED spots. The spots can be individually directed. When the spot is directed downwards, it can also be pushed upwards into the fixture opening so that it does not protrude beyond the frame.

- Easy installation with magnetic mounting
- Two individually adjustable spots with a 300mm spacing
- Available in matte black or matte white finish

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Driver positie</b>	Loose driver
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming
<b>Oriëntatie</b>	Down
<b>Shape</b>	Rectangular
<b>Isolatieklasse</b>	Class II
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Optics</b>	Lens
<b>Ambient temperature</b>	-20°C / +40°C
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Productkleur</b>	On request
<b>Bevestiging</b>	Recessed
<b>Kleurtemperatuur</b>	2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI97
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Kleurconsistentie (SDCM)</b>	SDCM=2
<b>Voltage / frequency</b>	220-240V, 50 / 60Hz
<b>Powerfactor</b>	>0.9
<b>Material</b>	Acrylic, Steel

