



## MESON ROUND 220 AQUA

Meson round 220 Aqua is an IP65 high-quality recessed downlight specifically designed for use above swimming pools and other wet areas. The cover and opal diffuser are made of plastic. The fixture is equipped with a set of three polyamide screws for mounting in suspended ceilings.

- IP65 housing (on the underside)
- Installation with a set of three polyamide screws
- Corrosion-free safety lighting
- White edge and opal polycarbonate diffuser

### Downloads

[Photometrics Meson aqua](#)

**Categories:** [Downlights and recessed spotlights](#)





**Downloads**

[Photometrics Meson aqua](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

|                                    |   |
|------------------------------------|---|
| <b>Isolatieklasse</b>              | Class II  |
| <b>Driver positie</b>              | Loose driver  |
| <b>Light control</b>               | 1-10V dimming, Casambi dimming, DALI dimming                                |
| <b>Producttoepassing</b>           | Education, Hospitality, Office, Public spaces                               |
| <b>Optics</b>                      | Opalen diffusor   |
| <b>Oriëntatie</b>                  | Down  |
| <b>Kleurtemperatuur</b>            | Tunable White, 2700K  |
| <b>Ambient temperature</b>         | -20°C / +40°C   |
| <b>Primaire aansluitingen</b>      | BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver |
| <b>Shape</b>                       | Round   |
| <b>Material</b>                    | Acrylic, Steel  |
| <b>Productkleur</b>                | On request  |
| <b>Bevestiging</b>                 | Recessed  |
| <b>Photobiological safety</b>      | IEC 62471: RG1 (low risc)   |
| <b>Color Rendering Index (CRI)</b> | CRI97, CRI90, CRI80   |
| <b>Emergency lighting</b>          | 1 hour emergency power, Optional, Optional 1 hour autonomy self-test        |
| <b>Family</b>                      | Meson   |
| <b>Kleurconsistentie (SDCM)</b>    | SDCM=2  |
| <b>Verwachte levensduur</b>        | L90B50@60,000h (Tq 25°C)  |
| <b>Powerfactor</b>                 | >0.9  |
| <b>Energielabel</b>                | A++   |

