



## **METRONOME-K**

Metronome-K is a linear LED luminaire equipped with 20, 28, or 36 lenses, recessed behind a grid louver. This LED luminaire offers a completely new lighting solution for effective illumination with an architectural aesthetic. A choice can be made between UGR < 19 optics (standard) and UGR < 16.

- Architectural aesthetic with 20, 28, or 36 optics
- Choice between UGR < 19 and UGR < 16 optics
- Louver finish white or high-gloss aluminum
- Flat design for shallow ceiling depths

### **Downloads**

[Photometrics Metronome-K](#)

**Categories:** [Climate ceiling fixtures](#)





**Downloads**

[Photometrics Metronome-K](#)

## NOTES

---

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Driver positie</b>	Attached to the fixture, Loose driver
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Shape</b>	Rectangular
<b>Energielabel</b>	A++
<b>Kleurtemperatuur</b>	Tunable White, 2700K
<b>Primaire aansluitingen</b>	BST 14i2, Europlug, On request, GST18i3, GST18i5 pastelblauw, On the driver
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Air extraction</b>	Optional
<b>Family</b>	Metronome
<b>Armaturefficiëntie</b>	>140lm/W
<b>Voltage / frequency</b>	220-240V, 50 / 60Hz
<b>Material</b>	Steel
<b>Powerfactor</b>	>0.9
<b>Bevestiging</b>	Recessed
<b>Optics</b>	Lens en louver
<b>Packaging dimensions</b>	Bulk packaging
<b>CIE Flux code</b>	96 99 100 100 100
<b>Isolatieklasse</b>	Class II
<b>Ambient temperature</b>	-20°C / +40°C
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Oriëntatie</b>	Down
<b>IP-class</b>	IP20 (upwards)/IP40 (downwards)
<b>Photobiological safety</b>	IEC 62471: RG1 (low risc)
<b>Specificaties</b>	G8A1 / 06-02-2025

